



Load Curve



AC | EPS

Down mode at 3speeds

Standard fork tilt device

CQDM12/15-810

1.2/1.5 Ton Counterbalanced Reach Stacker

Lifting Height: 1400-4500mm

Advantages

Configuration and Performance

- Fork tilt, double oil cylinder more smoothly.
- Electro-hydraulic integrated control, multi-function handle.
- Electronic power steering system, light and low noise.
- Two-way magnetic valve, three drop speed mode.
- AC Driving system, No carbon brush, maintenance free.
- USA CURTIS driving controller.
- Electromagnetic, regenerative braking system.
- Automatic lifting limit, proximity switch, long life.

Safety

- Curve automatic deceleration devices, more safe.
- Vehicle decelerates automatically at higher position.
- Stepless speed control system, safe and quiet.
- Controller with Multiple automatic protection.
- Emergency reversing device/Emergency brake switch.
- High position automatic reduction device.

Feature			
Model		CQDM12/15	CQDM12/15
Configuration No.		810	810
Type		Reach	Reach
Mast type		Standard 2-Stage	Full free 3-Stage
Load capacity	kg	1200/1500	1200/1500
Load center	mm	500	500
Wheel base	mm	1332	1332
Operating type		Walkie	Walkie
Wheels			
Wheels type		PU	PU
Wheel quantity Driving wheel/ Balance wheel/Bearing wheel		1/0/2	1/0/2
Dimension			
Reach distance	mm	0-425	0-425
Standard lift height	mm	1400/2000/2500/3000/3300/3600/4000	3700/3900/4200/4500
Max. extend height	mm	2235/2835/3335/3835/4135/4435/4835	4580/4780/5080/5380
Mast lowered height	mm	1490/1790/2040/2290/2440/2590/2790	1870/1940/2040/2140
Lowered fork height	mm	55	55
Fork size(length/width/thickness)	mm	1070/100/40	1070/100/40
Overall length	mm	2440/2896	2440/2896
Overall width	mm	1083	1083
Outside width between forks	mm	200-755	200-755
Tilt of fork(F/B)	mm	3/5	3/5
Min.Turning radius	mm	1596/2040	1596/2040
Min.Aisle width for pallets 800×1200		2620/3050	2620/3050
Min.Aisle width for pallets 1000×1200	km/h	2645/3075	2645/3075
Min.ground clearance	mm/s	60	60
Performance			
Travel speed,laden/unladen	%	5/5.5	5/5.5
Lift speed,laden/unladen		130/230	130/230
Lowering speed,laden/unladen	kW	130/230	130/230
Gradeability,laden/unladen	V	3/5	3/5
Electrical configuration			
Drive motor/Lift motor/Steering motor		AC1.5/DC3.0/DC0.15	AC1.5/DC3.0/DC0.15
Battery voltage		24	24
Battery capacity		280	280
Brake	kg	Electromagnetic/Regenerative	Electromagnetic/Regenerative
Controller	kg	CURTIS	CURTIS
Weight			
Battery weight		235	235
Service weight with battery		2100	2200

* Details of specifications and equipment are based on information available at time of printing and may change without notice.



ANHUI HELI INDUSTRIAL VEHICLE IMP. AND EXP. CO., LTD.

ADD: 668 FANGXING ROAD, HEFEI, ANHUI, CHINA

TEL: +8655163639068

FAX: +8655163639966

Email: heli@helichina.net

WEBSITE: WWW.HELICHINA.COM / WWW.HELICHINA.NET

Type	Lift height (mm)	Mast type	Outside width between forks (mm)	Inside width between forks (mm)
CQDM12/15-810	1400/2000/2500/3000/3300/3600/4000	Standard 2-STAGE	200-755	0-555
CQDM12/15-810	3700/3900/4200/4500	FULL FREE 3-STAGE		

Max lift height more than 3300,tilting device can not accept.